

4activeBS

The official Euro NCAP bicyclist target (EBT)

- ✓ standard average european utility bike average male
- ✓ realistic properties in size, shape and rotating wheels
- complies with ISO 19206-4, Euro NCAP, UN-ECE, ...

Allows testing under rough conditions

- ✓ extreme lightweight and soft structure to prevent damage on VUT
- ✓ robust and modular system easy and fast change of spare parts
- ☑ realistic response for Radar-, Lidar, Camera and IR-Systems

Available options

- ☑ bike for 7-year-old child
- different frame colours
- ✓ synchronized articulation (pedalling, arm signs, ...)





4activeBS

Performance

mono/stereo camera system, Lidar sensors	✓	
360° - Radar characteristic	✓	
micro-Doppler spread	✓	
near infrared / far infrared★	✓	
ultra-sonic	✓	
crash speed lateral / longitudinal	up to 60 km/h / up to 45 km/h	
operation speed	up to 35 km/h	
		★ optional

Dimensions bike

handlebar height	1200 mm
diameter wheels	700 mm
wheel base	1230 mm
weight	6 kg

Dimensions bicyclist

body height	1800 mm
shoulder width	500 mm
torso angle	10°
weight	< 4 kg

Key features

N

- ✓ compatible with 4activeSB, 4activeFB-small
- ✓ rotating wheels permanent contact to ground
- ✓ foldable bike easy transportation and storage
- ✓ extreme lightweight and soft structure

S