



I N P H Y S I C S W E T R U S T

## 4activeFB-large

**The best global solution fulfilling all Euro NCAP C2C specifications**

- ✓ to perform AEB/AES – CCRx and LSS scenarios
- ✓ compatible with vehicle target (GVT)
- ✓ very low RCS levels according to international standards/test protocols

**Fully synchronized operation with all relevant driving robots**

- ✓ real time position data from/to robot - import/export drive files
- ✓ corrects LAT/LONG waypoint errors of driving robots (VUT)
- ✓ full synchro mode - synchronization of 5 independent platforms

**Allows testing under rough conditions**

- ✓ traversable by heavy vehicles - trucks (40 tons)
- ✓ waterproof with IP67 protection
- ✓ precise performance at high speeds (up to 100 km/h)



# 4activeFB-large

## Performance

speed levels	50/80/100 km/h
acceleration longitudinal	+ 3m/s <sup>2</sup> / - 6 m/s <sup>2</sup> ★
acceleration lateral	± 3 m/s <sup>2</sup>
turning radius	7 m
ground clearance	0-15 mm
maximum payload	150 kg
battery charging time	~ 1 h★★
battery operating time	4a GVT > 4h (@50 km/h)★★★
positioning system	dual antenna dGNSS-IMU
dGNSS-RTK	L1/L2 GPS/GLONASS/BEIDOU
protection class	IP67
operation temperature range	-10° to 40° C (-20° to 55° C)★★★★

★depends on speed ★★at 20°C ★★★depending on acceleration ★★★★★additional test equipment available

## Dimensions

length	2400 mm
width	1400 mm
weight	155 kg

## Key features

- ✓ fast and easy battery swap system
- ✓ easy and efficient testing under worst conditions
- ✓ stealth technology - very low radar cross section
- ✓ traversable with full loaded 40 tons trucks
- ✓ Euro NCAP scenarios: AEB-CCRs/CCRm/CCRb, CCFtap, ELK, LSS

